

DTM Dry Toner Label Stock

Poly Transparent Gloss (RPTG)

Description

Poly Transparent Gloss label material has been designed specifically for use in labelling of the products requiring durability and resistance to chemicals or moisture on face material. Made of tough 50 µm polyester it comes with an topcoated surface which is suitable for printing by usual dry toner electrographic label printers, such as Primera's CX-Series, OKI's Pro10-Series and more.

Product Usage

All DTM Genuine certified dry toner materials are the ideal choice for labels printed on any electrographic label printer. Proper testing in the final application environment is recommended especially when used near water or chemicals. As with all pressure-sensitive materials, this product should be tested thoroughly under end-user conditions to ensure it will meet the requirements of the specific application.

Shelf Time

2 years when stored away from sunlight and heat, in a dark, dry place at a temperature of +20 °C with a relative humidity of 50%. Prolonged storage at higher temperatures and/or humidity levels will shorten the shelf life.

Technical Specifications

Face

Material:	Transparent, gloss coated heat stabilized polyester film
------------------	---

Basis Weight:	71 g/m ² DIN 53352
----------------------	-------------------------------

Thickness:	50 µm DIN 53370
-------------------	-----------------

Adhesive

Material:	Acrylic permanent
------------------	-------------------

Liner/Backing

Material:	White, woodfree kraft backing paper
------------------	-------------------------------------

Basis Weight:	100 g/m ² ISO 536
----------------------	------------------------------

Thickness:	97 µm ISO 534
-------------------	---------------

DTM Print GmbH
Mainzer Strasse 131
65187 Wiesbaden
Germany
Phone: +49 611 92777-0
Email: sales@dtm-print.eu
<http://dtm-print.eu>

