

DTM Dry Toner Label Stock

# Poly White Gloss (RPWG)

## Description

Poly White Gloss label material has been designed specifically for use in labelling of the products requiring durability and resistance to chemicals or moisture on face material. Made of tough 50 µm polyester it comes with an topcoated surface which is suitable for printing by usual dry toner electrographic label printers, such as Primera's CX-Series, OKI's Pro10-Series and more.

## Product Usage

All DTM Genuine certified dry toner materials are the ideal choice for labels printed on any electrographic label printer. Proper testing in the final application environment is recommended especially when used near water or chemicals. As with all pressure-sensitive materials, this product should be tested thoroughly under end-user conditions to ensure it will meet the requirements of the specific application.

## Shelf Time

2 years when stored away from sunlight and heat, in a dark, dry place at a temperature of +20 °C with a relative humidity of 50%. Prolonged storage at higher temperatures and/or humidity levels will shorten the shelf life.

## Technical Specifications

### Face

**Material:** White, gloss coated heat stabilised polyester film

**Basis Weight:** 72 g/m<sup>2</sup> ISO 536

**Thickness:** 50 µm ISO 534

### Adhesive

**Material:** Acrylic permanent

### Liner/Backing

**Material:** White, woodfree kraft backing paper for optimal layflat performance

**Basis Weight:** 120 g/m<sup>2</sup> ISO 536

**Thickness:** 112 µm ISO 534

### Performance

#### Minimum Application

**Temperature:** 5 °C

**Service Temperature:** -20 to 80 °C

DTM Print GmbH  
Mainzer Strasse 131  
65187 Wiesbaden  
Germany  
Phone: +49 611 92777-0  
Email: [sales@dtm-print.eu](mailto:sales@dtm-print.eu)  
<http://dtm-print.eu>

