

DTM Dry Toner Label Stock

# Paper Matte (RSG)

## Description

Paper Matte label material has been designed specifically for adhesion to cardboard, metals and most plastics. Matte finish is abrasion- and water-resistant. Comes with an topcoated surface which is suitable for printing by usual dry toner electrographic label printers, such as Primera's CX-Series, OKI's Pro10-Series and more.

## Product Usage

All DTM Genuine certified dry toner materials are the ideal choice for labels printed on any electrographic label printer. Proper testing in the final application environment is recommended especially when used near water or chemicals. As with all pressure-sensitive materials, this product should be tested thoroughly under end-user conditions to ensure it will meet the requirements of the specific application.

## Shelf Time

2 years when stored away from sunlight and heat, in a dark, dry place at a temperature of +20 °C with a relative humidity of 50%. Prolonged storage at higher temperatures and/or humidity levels will shorten the shelf life.

## Technical Specifications

### Face

**Material:** Woodfree machine finished paper

**Basis Weight:** 70 ± 2 g/m<sup>2</sup> ISO 536

**Thickness:** 89 ± 3 µm ISO 534

### Adhesive

**Material:** Acrylic permanent

### Liner/Backing

**Material:** White, woodfree kraft backing paper

**Basis Weight:** 66 ± 2 g/m<sup>2</sup> ISO 536

**Thickness:** 68 ± 3 µm ISO 534

DTM Print GmbH  
Mainzer Strasse 131  
65187 Wiesbaden  
Germany  
Phone: +49 611 92777-0  
Email: [sales@dtm-print.eu](mailto:sales@dtm-print.eu)  
<http://dtm-print.eu>

