

DTM DryToner Label Stock

# DTM Paper Top High Gloss (RTHG)

## Description

DTM DryToner Paper Top High Gloss label material has been designed specifically for adhesion to cardboard, metals and most plastics. High-gloss finish is very abrasion- and highly water-resistant. Comes with a topcoated surface which is suitable for printing by usual dry toner electrographic label printers, such as DTM CX86e, Primera's CX-Series, OKI's Pro10-Series and more.

## Face Stock

Cast-coated, wood-free paper with very glossy finish.

## Product Usage

All DTM Genuine certified dry toner materials are the ideal choice for labels printed on any electrographic label printer. Proper testing in the final application environment is recommended especially when used near water or chemicals. As with all pressure-sensitive materials, this product should be tested thoroughly under end-user conditions to ensure it will meet the requirements of the specific application.

## Shelf Time

2 years when stored away from sunlight and heat, in a dark, dry place at a temperature of +20 °C with a relative humidity of 50%. Prolonged storage at higher temperatures and/or humidity levels will shorten the shelf life.

## Technical Specifications

### Face

Material:	Paper	
Basis Weight:	80 ± 2 g/m <sup>2</sup>	ISO 536
Thickness:	78 ± 3 µm	ISO 534

### Adhesive

Material:	Acrylic, general purpose, water-borne permanent adhesive. Very low migration and bleeding characteristics	
-----------	--	--

### Liner/Backing

Material:	White, wood-free kraft backing paper	
Basis Weight:	66 ± 2 g/m <sup>2</sup>	ISO 536
Thickness:	69 ± 3 µm	ISO 534

### Performance

#### Minimum Application

Temperature:	5 °C
Service Temperature:	-10 to +100 °C

DTM Print GmbH  
Mainzer Strasse 131  
65187 Wiesbaden  
Germany  
Phone: +49 611 92777-0  
Email: [sales@dtm-print.eu](mailto:sales@dtm-print.eu)  
<http://dtm-print.eu>

